Nano2.5G Ethernet Transformers

Single Port 2.5GBASE-T Small Form Factor Isolation Modules





US Patent Numbers: 5,656,985 6,297,721 B1 6,297,720 B1 6,320,489 B1

6,344,785 B1 6,662.431 B1











Product Features:


- 2.5GBASE-T Miniature Package
- IEEE802.3bz/af/at/bt¹
- 4PPoE 4 Pair Power over Ethernet
- Robust Patented Open Frame Construction
- 1500Vrms Hi-Pot
- UL/EN60950 recognized
- 100% Compliance Testing

				Temp.	
Part Number	Data Rate	Total Power ²	Current Per Pair	Range	Turns Ratio
TG2G-S13NYNLF	2.5G	30W	350mA	0 to +70°C	1CT:1CT
TG2G-E13NYNLF	2.5G	30W	350mA	-40 to +85°C	1CT:1CT
TG2G-HPE3NYNLF	2.5G	60W	600mA	-40 to +85°C	1CT:1CT


0.450 -

Notes:

Package



Circuit



*Pins 13-24 located on line side

Dimensions: inch [mm]
Co-Planarity: 0.004 [0.10]

2880 Lakeside Drive #116 Santa Clara, CA 95054 (650) 903-3800 www.haloelectronics.com

HALO® Electronics is a leading supplier of high quality communication magnetics including signal transformers, filters, CMR chokes, PoE power transformers, DC/DC converters, and integrated Ethernet connectors. HALO's high quality leading edge technology solutions are manufactured in ISO9001 and ISO14001 factories.

¹ The IEEE802.3bt standard has not been officially ratified.

²Power rating reduced to half when using only two pairs for power as in 802.3af/802.3at applications. Please contact the factory or representative for individual datasheets or additional information.